






# TRI-R PRODUCT LINEUP


MODEL	T15A1104E27WW03	T15A1104E30WW03	T15A1104E40WW03	T15A1104E50WW03	
SIZE (mm)	15.0 x 12.0 x 1.5				
LIGHT SOURCE Dia. (mm)	8				
CRI (Typ.)	97				
CCT (K) *custom: 2000-6500	2,700	3,000	4,000	5,000	
WATTAGE (W)	6.6				
Vf (Typ. V)	34.6				
If (mA)	190				
LUMEN FLUX (Typ. lm)	590	605	640	655	
EFFICIENCY (Typ. lm/W)	90	92	97	100	

MODEL	T19A1109E27WW03	T19A1109E30WW03	T19A1109E40WW03	T19A1109E50WW03	
SIZE (mm)	19.0 x 16.0 x 1.5				
LIGHT SOURCE Dia. (mm)	12				
CRI (Typ.)	97				
CCT (K) *custom: 2000-6500	2,700	3,000	4,000	5,000	
WATTAGE (W)	14.9				
Vf (Typ. V)	34.6				
If (mA)	430				
LUMEN FLUX (Typ. lm)	1350	1390	1460	1490	
EFFICIENCY (Typ. lm/W)	91	93	98	100	

MODEL	T24A1114E27WW03	T24A1114E30WW03	T24A1114E40WW03	T24A1114E50WW03	
SIZE (mm)	24.0 x 20.0 x 1.5				
LIGHT SOURCE Dia. (mm)	15				
CRI (Typ.)	97				
CCT (K) *custom: 2000-6500	2,700	3,000	4,000	5,000	
WATTAGE (W)	23.2				
Vf (Typ. V)	34.6				
If (mA)	670				
LUMEN FLUX (Typ. lm)	2085	2150	2330	2370	
EFFICIENCY (Typ. lm/W)	90	93	101	102	

MODEL	T28A1130E27WW03	T28A1130E30WW03	T28A1130E40WW03	T28A1130E50WW03	
SIZE (mm)	28.0 x 28.0 x 1.5				
LIGHT SOURCE Dia. (mm)	22				
CRI (Typ.)	97				
CCT (K) *custom: 2000-6500	2,700	3,000	4,000	5,000	
WATTAGE (W)	49.5				
Vf (Typ. V)	34.6				
If (mA)	1430				
LUMEN FLUX (Typ. lm)	4460	4590	4830	4930	
EFFICIENCY (Typ. lm/W)	90	93	98	100	

MODEL	T35S0102J27WW03	T35S0102J30WW03	T35S0102J40WW03	T35S0102J50WW03	
SIZE (mm)	3.5 x 3.5 x 1.5				
LIGHT SOURCE Dia. (mm)	3.0				
CRI (Typ.)	97				
CCT (K) *custom: 2000-6500	2,700	3,000	4,000	5,000	
WATTAGE (W)	1.0				
Vf (Typ. V)	3.3				
If (mA)	300				
LUMEN FLUX (Typ. lm)	75	75	80	80	
EFFICIENCY (Typ. lm/W)	75	75	80	80	

MODEL	T30S0102J27WW03	T30S0102J30WW03	T30S0102J40WW03	T30S0102J50WW03	
SIZE (mm)	3.0 x 3.0				
April 2017 Release					